




LOW PRESSURE PAINTSPRAY HOSE

TYPE : **LPV**

TYPE : **LPC** (100% conductive)

TYPE : **LM** (transparent)

TYPE : **LMC** (transparent 100% conductive)



POLYAMIDE
POLYURETHANE LAYER
SYNTHETIC FIBER BRAID
POLYURETHANE

CONSTRUCTION:

Inner tube: Polyamide
Reinforcement: High tensile synthetic fibre yarn
Cover: Polyurethane, Colour or transparent

APPLICATION

Conventional paint spraying
Low pressure paint circulation and supply
Low pressure electrostatic lacquer system
Low pressure chemical product supply systems

Temperature range:

-40° C to 95° C, -40° F to 210° F

PROPERTIES

Excellent resistance to paints, solvents and chemicals (ref: Datasheet 299-87)
Excellent flexibility, flex-fatigue and non kinking
Abrasion, Ozone and UV resistant cover
Low flow resistance
High flow throughput
Small bend radius and very light weight
Long production length
Superior electrical conductivity for type LMC & LPC
Air and Water resistant

TECHNICAL SPECIFICATION EXITFLEX Type **LPV / LPC** with PU cover in Colour

DIMENSIONS		LPV / LPC 1.4	LPV / LPC 1.5	LPV / LPC 1.6	LPV / LPC 1.8
NOMINAL BORE METRIC		6	8	10	12
HOSE I.D.	Inch:	¼"	5/16"	3/8"	½"
HOSE I.D.	mm:	6,4	8,0	9,6	12,7
HOSE O.D.	mm:	11,8	13,8	15,5	19,0
MAXIMUM OPERATING PRESSURE	Bar	20	17	15	12
	Psi	290	250	220	175
MINIMUM BURST PRESSURE	Bar	80	70	60	50
	Psi	1170	1015	880	730
MINIMUM BEND RADIUS	mm	25	30	35	45
NOMINAL WEIGHT	g/m	95	115	135	190

TECHNICAL SPECIFICATION EXITFLEX Type **LM / LMC** with transparent PU cover

DIMENSIONS		LM / LMC 1.4	LM / LMC 1.5	LM / LMC 1.6
NOMINAL BORE METRIC		6	8	10
HOSE I.D.	Inch:	¼"	5/16"	3/8"
HOSE I.D.	mm:	6,4	8,0	9,6
HOSE O.D.	mm:	10,2	11,8	13,8
MAXIMUM OPERATING PRESSURE	Bar	20	17	15
	Psi	290	250	220
MINIMUM BURST PRESSURE	Bar	80	70	60
	Psi	1170	1015	880
MINIMUM BEND RADIUS	mm	25	30	35
NOMINAL WEIGHT	g/m	65	75	100

UPON SPECIAL REQUEST

- HOSE ASSEMBLIES are all fitted with white Zinc finished steel couplings swaged permanently to the hose.
- STANDARD COLOR: Blue or Black, other available in large quantities
- REMOVABLE STAINLESS STEEL couplings available
- WELDED TWINHOSE, 2 x Material or 1x Air+1x Mat.

All recommendations and suggestions appearing in this bulletin concerning the use of our products are based upon tests and data believed to be reliable. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Exit S.A., its subsidiaries, affiliates and distributors, as to the effects of such use or the results to be obtained, nor is any information to be construed as a recommendation to infringe any patent.